

LIGHTING
SOLUTIONS

2025

LNJAMI[®]
LIGHTING SOLUTIONS



Liangjia Beauty Lighting Co., Limited is a high-tech enterprise focusing on the research and development, manufacturing, sales and service of outdoor lighting products. We are committed to providing innovative, efficient and energy-saving lighting solutions for cities, commerce, landscapes and other fields, lighting up the world with light and improving the quality of life. We hope to become a global leading provider of outdoor lighting solutions, creating greater value for customers with high-quality products and professional services

Provide comprehensive and professional outdoor application lighting solutions

Our team of experts will work closely with you to ensure the solution provided perfectly meets your project needs and brings the best lighting results.

Lighting design

Illumination simulation

Debugging guidance
+
Selection and budget
+
Control and layout
+
Customized production

Contents



Case	03~04	LED Flood Light	
LED Pixel Point Light		TGF65	85~86
XS30	07~08	TGF80	87~88
XS40	09~10	TGF105	89~90
XS100	11~12	TGF130	91~92
XS200	13~14	TGF160	93~94
		TGF185	95~96
LED Mesh Screen Light		TGF220	97~98
XS18	17~18	TGF220L	99~100
		TGF405	101~102
LED Wall Washer		TGF645	103~104
XQ26F	21~22	TGD65	105~106
XQ28	23~24	TGD110	107~108
XQ35	25~26	TGD130	109~110
XQ45	27~28	TGD160	111~112
XQ56	29~30	TGD180	113~114
XQ30	31~32	TGD210	115~116
XQ40	33~34	TGD260	117~118
XQ40A	35~36	TGD300	119~120
XQ50	37~38	TG150-1A	121~122
XQ63	39~40	TG150-B	123~124
XQ80	41~42	TG150-C	125~126
		TGB	127~128
LED Linear Light		TGP	129~130
XT15C	45~46	TGH	131~132
XT15M	47~48	TGS	133~134
XT20S	49~50	MDD	135~148
XT20M	51~52	MDS	149~150
XT26C	53~54	MDN	151~152
XT26M	55~56	TPT	153~154
XT26G	57~58		
XT26B	59~60	LED Spotlight	
XT26AM	61~62	WL45	157~158
XT26AC	63~64	WL65	159~160
		SP65	161~162
LED Flexible Linear Light		SP75	163~164
RXQ1208	67~68	SP90	165~166
RXQ2010	69~70	SP108	167~168
RXQ2424	71~72		
RXT1616U	73~74	LED Inground Light	
RXT1616C	75~76	MD25	171~172
RXT1220C	77~78	MD60	173~174
RXT1405F	79~80	MD72	175~176
RXT1205W	81~82	MD50	177~178
		Md85	179~180
		MD130	181~182
		MD160	183~184
		MD180	185~186
		MD210	187~188
		MD230	189~190
		LED Guide Panel Light	
		DG600	193~194
		DG430	195~196
		LED Street Light	
		HL200	199~200
		HI300	201~202

Development Course

Project Cases

2008~2010

- Qingdao Olympic Sailing Base
- Beijing shopping Mall
- Anshan Shopping Mall
- Shengli Square
- Jiaxing ,Taiyuan Shopping Mall
- Qingdao Railway station,Zhineng & Futai Mansion,City government Hall
- Huzhou park ,zhengzhou Flyover




2011

- Qingdao Bay bridge
- Changxing central Avenue

2012~2013

- Dongying Huanghe River Park
- Jinan Highway,Beijing Sheraton Hotel
- Jinan Tourist area
- Nanchang Business Shopping Mall




2014

- Kunming Exhibition Hall
- Sichuan Bridge, Shuangliu Airport
- World Expo Spain Hal

2015~2016

- Heyuan Shopping Mall &Grand theater
- Beijing traffic Hall
- Chongqi Jiangbei Shopping Center
- Changzhou Shopping Center
- Nanjing Residential Building
- Shanghai Exhibition Hall
- Hunan City lighting project
- G20 Qianjiang River Project
- Qingdao Industrial Zone
- Beijing Tongzhou Bridge



2017

- Zhengzhou Erqi Memorial Hall
- Dongjie Business Center
- Xinan Wanda Shopping Mall
- Qingdao City Lighting Project



2018~2019


- Beijing Bridge
- Fuzhou Cloud Computing Center
- Nanjing Changjiang River
- Wuxi Railway Station
- Kunshan Shopping Center
- Qingdao Shopping Mall
- Beijing Business Center
- Wuyue Shopping Mall



2020

- Zhejiang Avenue
- Anhui Tongling Wuyue Shopping Mall
- Anhui Suzhou Wuyue Shopping Mall





LED Pixel Point Light

LED point light sources are widely used in the field of landscape lighting. They have saturated colors and uniform color mixing, and can perfectly present different color effects. When the building facade is laid on a large scale, it can be combined into a dot matrix screen and combined with an intelligent control system to achieve large-scale linkage and various patterns, animations, and text effects

XS30 LED pixel point light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XS30W3D2	0.9W	3000K/4000K/5700K	3*0.3W 3535	ON/OFF
XS30F3D2A	0.75W	RGB	3*0.25W 3535	DMX512
XS30F3D2B	0.9W	RGBW	3*0.3W 3535	DMX512



Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V
Size	L47*W34*H14mm
Housing Material	PC
Warranty	5 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension



Distribution curve flux




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ Adopt high-quality LED, high color rendering, high brightness, and uniform color;
- ※ The lamp body is made of high-quality PC material, which is UV-resistant, corrosion-resistant, non-discoloring, and has high light transmittance;
- ※ Waterproof male and female connectors, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node


Installation method 1



Installation method 2



Installation method 3



XS40 LED pixel point light




Electrical & output data



Item No.	Power	Color	LED Qty	Control method
XS40W6D2	1.2W	3000K/4000K/5700K	6*0.2W 3535	ON/OFF
XS40F6D2	1.2W	RGB	6*0.2W 3535	DMX512
XS40F8D2	1.8W	RGBW	8*0.2W 3535	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.



Dimension



Distribution curve flux




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ Adopt high-quality LED, high color rendering, high brightness, and uniform color;
- ※ The lamp body is made of high-quality PC material, which is UV-resistant, corrosion-resistant, non-discoloring, and has high light transmittance;
- ※ Waterproof male and female connectors, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node


Installation method 1



Installation method 2



Installation method 3



XS100 LED pixel point light



Electrical & output data





Item No.	Power	Color	LED Qty	Control method
XS100W18D2	5W	3000K/4000K/5700K	18*0.3W 2835	ON/OFF
XS100F18D2	5W	RGBW	18*0.3W 5050	DMX512
XS110W18D2	5W	3000K/4000K/5700K	18*0.3W 2835	ON/OFF
XS110F18D2	5W	RGBW	18*0.3W 5050	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L119*W104*H72mm L112*W112*H69mm
Housing Material	ADC12+ Glass Cover ADC12+ PC Cover
Warranty	5 Years
Beam Angle	110°/130°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension





Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ Adopt high-quality LED, high color rendering, high brightness, and uniform color;
- ※ The lamp body is made of high-quality PC material, which is UV-resistant, corrosion-resistant, non-discoloring, and has high light transmittance;
- ※ Waterproof male and female connectors, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



XS200 LED pixel point light




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XS200W15D2	15W	3000K/4000K/5700K	15*1W 3030	ON/OFF
XS200F18D2	20W	RGBW	18*1.5W 5050	DMX512



Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V
Size	L203*W179*H101mm
Housing Material	ADC12+ Transparent PC Cover ADC12+ Milk white PC Cover
Warranty	5 Years
Beam Angle	110°/130°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension





Distribution curve flux




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ Adopt high-quality LED, high color rendering, high brightness, and uniform color;
- ※ The lamp body is made of high-quality PC material, which is UV-resistant, corrosion-resistant, non-discoloring, and has high light transmittance;
- ※ Waterproof male and female connectors, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node






LED Mesh Screen Light

The grid screen is a grid-shaped display screen, which has the characteristics of a point light source and the effect of a display screen. Its main advantages are: high protection level, suitable for various outdoor environments; high transmittance, outdoor building curtain wall use, does not affect the appearance of the curtain wall. The screen is made of flexible material and can be used in various uneven installation environments and shapes; and the grid screen is spliced with unit blocks, which has the advantages of fast construction, fast installation, and can be cut.

XS18 LED Mesh screen light




Electrical & output data


Pixel pitch	P31.25	P40	P50	P55	P62.5	P80	100	P125	P150
Pixels/square	1024	625	400	331	256	156	100	64	44
Permeability	43.8%	60.3%	70.6%	74.0%	78.0%	83.8%	87.6%	90.5%	92.3%
Brightness	6554	4000	2560	2116	1638	1000	640	410	284

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Distribution curve flux





Product Features

- ※ Each color has 65536 levels of grayscale, 4K refresh rate;
- ※ Special sealant potting, protection level IP67;
- ※ It has good transmittance without blocking the light, soft and flexible, free splicing;
- ※ It adopts the bad pixel retransmission function of dual-channel signal input, and the bad pixel does not affect the signal transmission;
- ※ It can be planned and customized as a whole according to the shape and size of the project, and can be cut.


Install Node



Dimension



$$A=31/40/50/62.5/80/100/125/150$$



LED Wall Washer

Outdoor wall washer is a common outdoor lighting equipment, mainly used to illuminate building exterior walls or landscape walls. It has a waterproof and dustproof design and can adapt to harsh external environments while providing good lighting and decorative effects. Illuminate the outline or details of the building's exterior wall to highlight the beauty and three-dimensionality of the building.

XQ26F LED Wall Washer




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ26FW48D2	12W	White	48*0.25W	ON/OFF
XQ26FW48D2	15W	White	48*0.3W	ON/OFF
XQ26FF48D2	12W	RGB	48*0.25W	DMX512
XQ26FF48D2	15W	RGBW	48*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V
Size	L1000*W26*H59mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	30°/45°/20°/40°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.

Install Node



XQ28 LED Wall Washer





Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ28W24D2	24W	White	24*1W	ON/OFF
XQ28F24D2	24W	RGBW	18*1.5W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W28*H41mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	20°/30°/45°/20*40°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C, Tamax=55 °C
Luminous efficiency	WHITE 80lm/w, RGBW 40lm/w
RH	30~80%



Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.



Distribution curve flux



Install Node



XQ35 LED Wall Washer




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ35W24D2	24W	White	24*1W	ON/OFF
XQ35W30D2	30W	White	30*1W	ON/OFF
XQ35F18D2	24W	RGBW	18*1.5W	DMX512
XQ35F24D2	36W	RGBW	24*1.5W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V
Size	L1000*W35*H48mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/45°/60°/15°25°/10°60°/15°35°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.

Install Node



XQ45 LED Wall Washer




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ45W36D2	36W	White	36*1W	ON/OFF
XQ45F24D2	36W	RGB	24*1.5W	DMX512
XQ45F24D2	48W	RGBW	24*2W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	L1000-W45*H68mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/45°/60°/15*25°/10*60°/15*35°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.



Distribution curve flux



Install Node



XQ56 LED Wall Washer





Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ56W36D2	72W	White	36*2W	ON/OFF
XQ56F24D2	48W	RGB	24*2W	DMX512
XQ56F24D2	72W	RGBW	24*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Voltage	DC24V/AC110~240V
Size	L1000*W56*H86mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/45°/60°/15*25°/10*60°/15*35°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w, RGBW 40lm/w
RH	30~80%

Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.

Install Node



XQ30 LED Wall Washer



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ28W24D2	24W	White	24*1W	ON/OFF
XQ30F24D2	24W	RGBW	18*1.5W	DMX512
XQ30F36D2	36W	RGBW	18*2W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	L1000*W30*H64mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	20°/30°/45°/20*40°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.


Distribution curve flux



Install Node



XQ40 LED Wall Washer



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ40W24D2	36W	White	24*1.5W	ON/OFF
XQ40F24D2	36W	RGB	24*2W	DMX512
XQ40F24D2	48W	RGBW	24*2W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	L1000*W40*H68mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/55°/60°/15°25°/10°60°/15°35°/15°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.




Distribution curve flux



Install Node







Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ40AW36D2	36W	White	36*1W	ON/OFF
XQ40AF24D2	48W	RGBW	24*2W	DMX512
XQ40AW36A4	36W	White	36*1W	ON/OFF
XQ40AF36A4	48W	RGBW	24*2W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC110~240V
Size	L1000*W40*H96mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/45°/60°/15*25°/10*60°/15*35°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Distribution curve flux



Install Node



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.

XQ50 LED Wall Washer



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ50W36D2	72W	White	36*2W	ON/OFF
XQ50F24D2	72W	RGBW	24*3W	DMX512
XQ50W36A4	72W	White	36*2W	ON/OFF
XQ50F24A4	72W	RGBW	24*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	L1000*W50*H80mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/45°/60°/15*25°/10*60°/15*35°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.



Distribution curve flux



Install Node



XQ63 LED Wall Washer



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XQ63W24D2	84W	White	24*3.5W	ON/OFF
XQ63F24D2	96W	RGBW	24*4W	DMX512
XQ63W24A4	84W	White	24*3.5W	ON/OFF
XQ63F24DA4	96W	RGBW	24*4W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC110~240V
Size	L1000*W63*H109mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/30°/45°/60°/15*25°/10*60°/15*35°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%˚



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Surface treatment Aksu powder; and high-quality spraying process, corrosion resistance, no discoloration;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility;
- ※ Conventional length 1M, 0.5M, 0.3M, other sizes can be customized.

Install Node




XQ80 LED Wall Washer



Voltage	DC24V/AC110~240V
Size	L1000*W80*H107mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	5°/30°/5+12°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XQ80W40A4	120W	White	40*3W	ON/OFF
XQ80F40A4	120W	RGBW	40*3W	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Distribution curve flux



Install Node





LED Linear Light

Outdoor linear lights are outdoor lighting equipment with straight or flexible curve shapes. They use high-brightness LED lamp beads to present rich light effects. They are also waterproof, dustproof and durable. Outdoor linear lights can be used to illuminate the contour lines of the building, highlight the shape and structure of the building, and create a unique visual effect at night.

XT15C LED linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT15CW48D2	12W	White	48*0.25W	ON/OFF
XT15CF48D2	12W	RGB	48*0.25W	DMX512
XT15CF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W15*H30mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension






Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



XT15M LED linear light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XT15MW60D2	12W	White	48*0.25W	ON/OFF
XT15MF60D2	12W	RGB	48*0.25W	DMX512
XT15MF60D2	15W	RGBW	48*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W15*H42mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension






Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Distribution curve flux



Install Node




XT20S LED linear light



Voltage	DC24V
Size	L1000*W20*H55mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT20SW48D2	12W	White	48*0.25W	ON/OFF
XT20SF48D2	12W	RGB	48*0.25W	DMX512
XT20SF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



XT20M LED linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT20MW48D2	12W	White	48*0.25W	ON/OFF
XT20MF48D2	12W	RGB	48*0.25W	DMX512
XT20MF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W20*H56mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	130°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



XT26C LED linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT26CW48D2	12W	White	48*0.25W	ON/OFF
XT26CF48D2	12W	RGB	48*0.25W	DMX512
XT26CF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W26*H32mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%


Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Distribution curve flux



Install Node



XT26M LED linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT26MW48D2	12W	White	48*0.25W	ON/OFF
XT26MF48D2	12W	RGB	48*0.25W	DMX512
XT26MF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W26*H49mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension






Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



XT26G LED linear light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
XT26GF48D2	12W	RGB	48*0.25W	DMX512
XT26GF48D2	15W	RGBW	48*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W26*H31mm
Housing Material	AL6063
Warranty	5 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%





Distribution curve flux




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



Dimension




XT26B LED linear light



Voltage	DC24V
Size	L1000*W26*H42mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT26BW48D2	12W	White	48*0.25W	ON/OFF
XT26BF48D2	12W	RGB	48*0.25W	DMX512
XT26BF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.






Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor special tempered glass material, which is anti-ultraviolet, anti-yellowing and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Install Node



XT26AM LED linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT26AMW48D2	12W	White	48*0.25W	ON/OFF
XT26AMF48D2	12W	RGB	48*0.25W	DMX512
XT26AMF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W26*H42mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%


Dimension






Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Distribution curve flux



Install Node



XT26AC LED linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
XT26ACW48D2	12W	White	48*0.25W	ON/OFF
XT26ACF48D2	12W	RGB	48*0.25W	DMX512
XT26ACF48D2	15W	RGBW	48*0.3W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W26*H42mm
Housing Material	AL6063+PC
Warranty	5 Years
Beam Angle	60°/120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%


Dimension






Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength 6063 aluminum alloy, with good thermal conductivity and excellent heat dissipation;
- ※ The luminous surface is made of outdoor-specific PC material, which is resistant to UV rays, yellowing, and has high light transmittance;
- ※ High-quality LED is used, with high color rendering, high brightness, and uniform color;
- ※ The surface is treated with Akzo powder and high-quality spraying technology, which is corrosion-resistant and does not change color.
- ※ Waterproof male and female plugs, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility

Distribution curve flux




Install Node



LED Flexible Linear Light

It has beautiful appearance, strong decorative effect, and has the illumination and product functions of traditional wall washer lamps. It is a high-end flexible decorative lamp. It has better waterproof, UV resistance and anti-oxidation performance, and can be bent straight or sideways. The installation is more firm and stable, and it can be used better and more widely in various places where lighting is needed.



RXQ1208 LED Flexible linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
RXQ1208W56D2	15W	White	56*0.26W	ON/OFF
RXQ1208W56D2	15W	White	56*0.26W	DMX512
RXQ1208F56D2	15W	RGB	56*0.26W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W12*H8mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	30°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%


Dimension




Product Features

- ※ Can supply power up to 5 meters at the single end;
- ※ High transmittance 95%, Resistance to trample IK08, low temperature resistant-45°;
- ※ Excellent weather resistance, salt and alkali resistance, anti UV4.5, high flameretardant V2;
- ※ Colors are available;
- ※ Branded lumileds light source.

Distribution curve flux



Install Node



RXQ2010 LED Flexible linear light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
RXQ2010W48D2	24W	White	48*0.5W	ON/OFF
RXQ2010W24D2	18W	White	24*0.75W	DMX512
RXQ2010F48D2	24W	RGB	48*0.5W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W20*H10mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	15°/30°/45°/60°/25*45°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%


Dimension




Product Features

- ※ Can supply power up to 5 meters at the single end;
- ※ High transmittance 95%, Resistance to trample IK08, low temperature resistant-45°;
- ※ Excellent weather resistance, salt and alkali resistance, anti UV4.5, high flameretardant V2;
- ※ Colors are available;
- ※ Branded lumileds light source.

Distribution curve flux



Install Node



RXQ2424 LED Flexible linear light



Electrical & output data



Item No.	Power	Color	LED Qty	Control method
RXQ2424W36D2	24W	White	36*0.67W	ON/OFF
RXQ2424F36D2	24W	RGBW	36*0.67W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W24*H24mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	30°/40°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



One bin



High Grayscale



IP66



Outdoor



Class III




CE




DMX512



IK 06



Distribution curve flux





Product Features

- ※ Can supply power up to 5 meters at the single end;
- ※ High transmittance 95%, Resistance to trample IK08, low temperature resistant-45°;
- ※ Excellent weather resistance, salt and alkali resistance, anti UV4.5, high flameretardant V2;
- ※ Colors are available;
- ※ Branded lumileds light source.


Install Node




Aluminum card slot



3D bendable card slot



RXT1616U LED Flexible linear light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
RXT1616UW60D1	12W	White	60*0.2W	ON/OFF
RXT1616UF60D1	15W	RGBW	60*0.25W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W16*H16mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※The DMX512 outdoor flexible light strip has good flexibility;
- ※It can be bent and folded according to the building installation structure on the project site;
- ※The product is small in size and easy to install and hide on site;
- ※The luminous surface of the product is uniform and has no glare and soft light, presenting a better visual effect;
- ※The product has a breakpoint resume function, which saves time and cost for installation and later maintenance.

Distribution curve flux



Install Node




RXT1616C LED Flexible linear light



Voltage	DC24V
Size	L1000*W16*H16mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
RXT1616CW60D1	12W	White	120*0.1W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Product Features


- ※The DMX512 outdoor flexible light strip has good flexibility;
- ※It can be bent and folded according to the building installation structure on the project site;
- ※The product is small in size and easy to install and hide on site;
- ※The luminous surface of the product is uniform and has no glare and soft light, presenting a better visual effect;
- ※The product has a breakpoint resume function, which saves time and cost for installation and later maintenance.




Distribution curve flux



Install Node



RXT1220C LED Flexible linear light





Electrical & output data

Item No.	Power	Color	LED Qty	Control method
RXT1220CW60D1	12W	White	60*0.2W	ON/OFF
RXT1220CW60D2	15W	RGBW	60*0.25W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W12*H20mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C, Tamax=55 °C
Luminous efficiency	WHITE 80lm/w, RGBW 40lm/w
RH	30~80%



Dimension




Product Features


- ※The DMX512 outdoor flexible light strip has good flexibility;
- ※It can be bent and folded according to the building installation structure on the project site;
- ※The product is small in size and easy to install and hide on site;
- ※The luminous surface of the product is uniform and has no glare and soft light, presenting a better visual effect;
- ※The product has a breakpoint resume function, which saves time and cost for installation and later maintenance.



Distribution curve flux



Install Node




RXT1405F LED Flexible linear light



Voltage	DC24V
Size	L1000*W14*H5mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
RXT1405F60D2	15W	RGBW	60*0.25W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Distribution curve flux



Product Features

- ※Multiple waterproof designs;
- ※Good toughness, high transparency, good adhesion;
- ※Long service life;
- ※The product has breakpoint resume function;
- ※Installation and subsequent maintenance greatly save time and cost.

Install Node




RXT1205W LED Flexible linear light



Voltage	DC24V
Size	L1000*W12*H5mm
Housing Material	Silicone Rubber
Warranty	2 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
RXT1205W60D2	12W	White	60*0.2W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.




Distribution curve flux




Product Features

- ※Multiple waterproof designs;
- ※Good toughness, high transparency, good adhesion;
- ※Long service life;
- ※The product has breakpoint resume function;
- ※Installation and subsequent maintenance greatly save time and cost.

Install Node





LED Flood Light

Outdoor floodlights are widely used, and suitable types and functional lighting can be selected according to different needs and scenarios. They not only provide functional lighting, but also can focus on certain objects that need to be highlighted, emphasize the unique texture of the building, form a primary and secondary relationship, create a unique atmosphere and visual effects, and add charm and highlights to the outdoor environment.

TGF65 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF65W4D2	8W	White	4*2W	ON/OFF
TGF65F4D2	12W	RGBW	4*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC110~240V
Size	L65*W65*H99mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TGF80 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF80W5D2	12W	White	5*2.4W	ON/OFF
TGF80F5D2	15W	RGBW	5*3W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage DC24V/AC110~240V

Size L80*W80*H116mm

Housing Material ADC12 + Tempered Glass

Warranty 5 Years

Beam Angle 10°/30°/45°/15°25°/20°45°/10°60°

CRI >80

SDCM <5

Ambient temperature Tamin=-20 °C, Tamax=55 °C

Luminous efficiency WHITE 80lm/w, RGBW 40lm/w

RH 30~80%



One bin



Class III



High Grayscale



Class I



IP66



DALI/O~10V




Outdoor




IK 06

Dimension



Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TGF105 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF105W8D2	18W	White	8*2.25W	ON/OFF
TGF105F8D2	24W	RGBW	8*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	L105*W105*H154mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGF130 LED flood light




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF130W12D2	24W	White	12*2W	ON/OFF
TGF130F12D2	36W	RGBW	12*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	L130*W130*H179mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGF160 LED flood light




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF160W16A4	36W	White	16*2.25W	ON/OFF
TGF160F16A4	48W	RGBW	16*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	L160*W160*H218mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGF185 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF185W24A4	48W	White	24*2W	ON/OFF
TGF185F24A4	72W	RGBW	24*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	L185*W185*H247mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Distribution curve flux



Install Node



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

TGF220 LED flood light




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF220W36A4	72W	White	36*2W	ON/OFF
TGF220F36A4	96W	RGBW	36*2.7W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	L220*W220*H291mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension





Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TGF220L LED flood light




Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF220LW48A4	100W	White	48*2.1W	ON/OFF
TGF220LF48A4	120W	RGBW	48*2.5W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	L220*W220*H307mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Distribution curve flux



Install Node



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

TGF405 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF405W60A4	120W	White	60*2W	ON/OFF
TGF405F60A4	150W	RGBW	60*2.5W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	L404*W196*H322mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGF645 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGF645W112A4	300W	White	112*2.7W	ON/OFF
TGF645F112A4	360W	RGBW	112*3.2W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	L643*W215*H301mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD65 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD65W3D2	6W	White	3*2W	ON/OFF
TGD65F3D2	9W	RGBW	3*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	Ø65*W80*H94mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD110 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD110W6D2	12W	White	6*2W	ON/OFF
TGD110F6D2	18W	RGBW	6*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	Ø110*W119*H153mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD130 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD130W12D2	24W	White	12*2W	ON/OFF
TGD130F12D2	36W	RGBW	12*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC110~240V
Size	Ø130*W136*H172mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD160 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD160W18A4	36W	White	18*2W	ON/OFF
TGD160F18A4	54W	RGBW	18*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	Ø160*W172*H213mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD180 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD180W24A4	60W	White	24*2.5W	ON/OFF
TGD180F24A4	72W	RGBW	24*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	Ø180*W180*H242mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD210 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD210W36A4	80W	White	36*2.2W	ON/OFF
TGD210F36A4	96W	RGBW	36*2.7W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	Ø210*W223*H273mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node








Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD260W60A4	120W	White	60*2W	ON/OFF
TGD260F60A4	150W	RGBW	60*2.5W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100-240V
Size	Ø268*W140*H331mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	5°/10°/30°/45°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TGD300 LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGD300W72A4	150W	White	72*2W	ON/OFF
TGD300F72A4	200W	RGBW	72*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	Ø306*W145*H381mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	5°/10°/30°/45°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TG150-1A LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TG150-1A	18W	White	16*1W 3030	ON/OFF
TG150-1A	30W	White	16*2W 3535	ON/OFF
TG150-1A	36W	RGBW	16*2W 3535	DMX512
TG150-2A	72W	RGBW	32*2W 3535	DMX512
TG150-4A	120W	RGBW	64*2W 3535	DMX512
TG150-4A*2	240W	RGBW	128*2W 3535	DMX512
TG150-4A*3	360W	RGBW	192*2W 3535	DMX512
TG150-5A*3	500W	RGBW	240*2W 3535	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	L186/298/524/580/577/690*W149*H100mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	10°/17°/25°/40°/60°/10*22/12*45/15*55°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength AL6063 aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TG150-B LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TG150-1B	24W	White	24*1W 3030	ON/OFF
TG150-1B	36W	White	24*1.5W 3535	ON/OFF
TG150-2B	48W	White	48*1W 3030	ON/OFF
TG150-2B	72W	White	48*1.5W 3535	ON/OFF
TG150-3B	120W	White	72*1.5W 3535	ON/OFF
TG150-3B*2	240W	White	144*1.5W 3535	ON/OFF
TG150-3B*3	360W	White	216*1.5W 3535	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	L237/402/567/623*W149*H100mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	15°/ 30°/45°/60°/15*35°/15*45°/15*60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength AL6063 aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TG150-C LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TG150-1C	24W	White/RGBW	9*3W 3535	ON/OFF DMX512
TG150-2C	48W	White/RGBW	18*3W 3535	ON/OFF DMX512
TG150-3C	72W	White/RGBW	27*3W 3535	ON/OFF DMX512
TG150-4C	100W	White/RGBW	36*3W 3535	ON/OFF DMX512
TG150-4C*2	200W	White/RGBW	72*3W 3535	ON/OFF DMX512
TG150-4C*3	300W	White/RGBW	108*3W 3535	ON/OFF DMX512
TG150-5C*3	400W	White/RGBW	135*3W 3535	ON/OFF DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100-240V
Size	L188/302/416/530/586/700*W149*H100mm
Housing Material	AL6063+Tempered Glass
Warranty	5 Years
Beam Angle	5°/10°/25°/40°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w, RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength AL6063 aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node





Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGB135F9A4	24W	White/RGBW	9*3W	ON/OFF DMX512
TGB155F12A4	36W	White/RGBW	12*3W	ON/OFF DMX512
TGB175F18A4	48W	White/RGBW	18*3W	ON/OFF DMX512
TGB200F24A4	60W	White/RGBW	24*2.5W	ON/OFF DMX512
TGB220F36A4	72W	White/RGBW	36*2W	ON/OFF DMX512
TGB265F60A4	120W	White/RGBW	60*2W	ON/OFF DMX512



Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC100~240V
Size	Ø135,155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15*25°/20*45°/10*60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.


Install Node





Voltage	DC24V/AC100~240V
Size	Ø135,155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
TGP135F9A4	24W	White/RGBW	9*3W	ON/OFF DMX512
TGP155F12A4	36W	White/RGBW	12*3W	ON/OFF DMX512
TGP175F18A4	48W	White/RGBW	18*3W	ON/OFF DMX512
TGP200F24A4	60W	White/RGBW	24*2.5W	ON/OFF DMX512
TGP220F36A4	72W	White/RGBW	36*2W	ON/OFF DMX512
TGP265F60A4	120W	White/RGBW	60*2W	ON/OFF DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.



Distribution curve flux



Install Node





Electrical & output data

Item No.	Power	Color	LED Qty	Control method	
TGH155F12A4	36W	White/RGBW	12*3W	ON/OFF	DMX512
TGH175F18A4	48W	White/RGBW	18*3W	ON/OFF	DMX512
TGH200F24A4	60W	White/RGBW	24*2.5W	ON/OFF	DMX512
TGH220F36A4	72W	White/RGBW	36*2W	ON/OFF	DMX512
TGH265F60A4	120W	White/RGBW	60*2W	ON/OFF	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC100~240V
Size	Ø155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15*25°/20*45°/10*60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node





Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TGS155F12A4	36W	hite/RGBW	12*3W	ON/OFF DMX512
TGS175F18A4	48W	White/RGBW	18*3W	ON/OFF DMX512
TGS200F24A4	60W	White/RGBW	24*2.5W	ON/OFF DMX512
TGS220F36A4	72W	White/RGBW	36*2W	ON/OFF DMX512
TGS265F60A4	120W	White/RGBW	60*2W	ON/OFF DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC100~240V
Size	Ø155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15*25°/20*45°/10*60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Distribution curve flux



Install Node





Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MDD155F12A4	36W	White/RGBW	12*3W	ON/OFF DMX512
MDD175F18A4	48W	White/RGBW	18*3W	ON/OFF DMX512
MDD200F24A4	60W	White/RGBW	24*2.5W	ON/OFF DMX512
MDD220F36A4	72W	White/RGBW	36*2W	ON/OFF DMX512
MDD265F60A4	120W	White/RGBW	60*2W	ON/OFF DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC100~240V
Size	Ø155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15*25°/20*45°/10*60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node





Electrical & output data

Item No.	Power	Color	LED Qty	Control method	
MDS155F12A4	36W	White/RGBW	12*3W	ON/OFF	DMX512
MDS175F18A4	48W	White/RGBW	18*3W	ON/OFF	DMX512
MDS200F24A4	60W	White/RGBW	24*2.5W	ON/OFF	DMX512
MDS220F36A4	72W	White/RGBW	36*2W	ON/OFF	DMX512
MDS265F60A4	120W	White/RGBW	60*2W	ON/OFF	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC100~240V
Size	Ø135,155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15*25°/20*45°/10*60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.


Distribution curve flux



Install Node



Dimension



MDN LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MDN135F9A4	24W	White/RGBW	9*3W	ON/OFF DMX512
MDN155F12A4	36W	White/RGBW	12*3W	ON/OFF DMX512
MDN175F18A4	48W	White/RGBW	18*3W	ON/OFF DMX512
MDN200F24A4	60W	White/RGBW	24*2.5W	ON/OFF DMX512
MDN220F36A4	72W	White/RGBW	36*2W	ON/OFF DMX512
MDN265F60A4	120W	White/RGBW	60*2W	ON/OFF DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V/AC100~240V
Size	Ø135,155,175,200,220,265mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Distribution curve flux



Install Node



TPT LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TPT65W3A4-A	8W	White	3*2.7W	ON/OFF
TPT65F3A4-A	12W	RGBW	3*4W	DMX512
TPT65W3A4-B	8W	White	3*2.7W	ON/OFF
TPT65F3A4-B	12W	RGBW	3*4W	DMX512
TPT65W3A4-C	8W	White	3*2.7W	ON/OFF
TPT65F3A4-C	12W	RGBW	3*4W	DMX512
TPT65W3A4-D	8W	White	3*2.7W	ON/OFF
TPT65F3A4-D	12W	RGBW	3*4W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100~240V
Size	Ø66mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux





Install Node





Item No.	Power	Color	LED Qty	Control method
TPT85W6A4-A	15W	White	6*2.5W	ON/OFF
TPT85F6A4-A	24W	RGBW	6*4W	DMX512
TPT85W6A4-B	15W	White	6*2.5W	ON/OFF
TPT85F6A4-B	24W	RGBW	6*4W	DMX512
TPT85W6A4-C	15W	White	6*2.5W	ON/OFF
TPT85F6A4-C	24W	RGBW	6*4W	DMX512
TPT85W6A4-D	15W	White	6*2.5W	ON/OFF
TPT85F6A4-D	24W	RGBW	6*4W	DMX512

Voltage	AC100~240V
Size	ø84mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



The image displays four different models of outdoor spotlights, labeled Type-A through Type-D, arranged horizontally. A dashed line indicates the ground level. Type-A is a low-profile spotlight with a short mounting arm. Type-B is a tall spotlight with a long, slender pole. Type-C is a spotlight mounted on a long, thin stake. Type-D is a low-profile spotlight mounted on a shorter stake. All spotlights have a cylindrical head with four visible LED chips.

TPT LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TPT100W9A4-A	24W	White	9*2.7W	ON/OFF
TPT100F9A4-A	36W	RGBW	9*4W	DMX512
TPT100W9A4-B	24W	White	9*2.7W	ON/OFF
TPT100F9A4-B	36W	RGBW	9*4W	DMX512
TPT100W9A4-C	24W	White	9*2.7W	ON/OFF
TPT100F9A4-C	36W	RGBW	9*4W	DMX512
TPT100W9A4-D	24W	White	9*2.7W	ON/OFF
TPT100F9A4-D	36W	RGBW	9*4W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	AC100~240V
Size	Ø101mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



TPT LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TPT120W12A4-A	36W	White	12*3W	ON/OFF
TPT120F12A4-A	48W	RGBW	12*4W	DMX512
TPT120W12A4-B	36W	White	12*3W	ON/OFF
TPT120F12A4-B	48W	RGBW	12*4W	DMX512
TPT120W12A4-C	36W	White	12*3W	ON/OFF
TPT120F12A4-C	48W	RGBW	12*4W	DMX512
TPT120W12A4-D	36W	White	12*3W	ON/OFF
TPT120F12A4-D	48W	RGBW	12*4W	DMX512
TPT120W12A4-E	36W	White	12*3W	ON/OFF
TPT120F12A4-E	48W	RGBW	12*4W	DMX512
TPT120W12A4-F	36W	White	12*3W	ON/OFF
TPT120F12A4-F	48W	RGBW	12*4W	DMX512
TPT120W12A4-G	36W	White	12*3W	ON/OFF
TPT120F12A4-G	48W	RGBW	12*4W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100~240V
Size	Ø120mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TPT LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TPT140W18A4-A	48W	White	18*2.7W	ON/OFF
TPT140F18A4-A	60W	RGBW	18*3.3W	DMX512
TPT140W18A4-B	48W	White	18*2.7W	ON/OFF
TPT140F18A4-B	60W	RGBW	18*3.3W	DMX512
TPT140W18A4-C	48W	White	18*2.7W	ON/OFF
TPT140F18A4-C	60W	RGBW	18*3.3W	DMX512
TPT140W18A4-D	48W	White	18*2.7W	ON/OFF
TPT140F18A4-D	60W	RGBW	18*3.3W	DMX512
TPT140W18A4-E	48W	White	18*2.7W	ON/OFF
TPT140F18A4-E	60W	RGBW	18*3.3W	DMX512
TPT140W18A4-F	48W	White	18*2.7W	ON/OFF
TPT140F18A4-F	60W	RGBW	18*3.3W	DMX512
TPT140W18A4-G	48W	White	18*2.7W	ON/OFF
TPT140F18A4-G	60W	RGBW	18*3.3W	DMX512



Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100~240V
Size	Ø144mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TPT LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TPT160W24A4-A	60W	White	24*2.5W	ON/OFF
TPT160F24A4-A	72W	RGBW	24*3W	DMX512
TPT160W24A4-B	60W	White	24*2.5W	ON/OFF
TPT160F24A4-B	72W	RGBW	24*3W	DMX512
TPT160W24A4-C	60W	White	24*2.5W	ON/OFF
TPT160F24A4-C	72W	RGBW	24*3W	DMX512
TPT160W24A4-D	60W	White	24*2.5W	ON/OFF
TPT160F24A4-D	72W	RGBW	24*3W	DMX512
TPT160W24A4-E	60W	White	24*2.5W	ON/OFF
TPT160F24A4-E	72W	RGBW	24*3W	DMX512
TPT160W24A4-F	60W	White	24*2.5W	ON/OFF
TPT160F24A4-F	72W	RGBW	24*3W	DMX512
TPT160W24A4-G	60W	White	24*2.5W	ON/OFF
TPT160F24A4-G	72W	RGBW	24*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100~240V
Size	Ø163mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



TPT LED flood light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
TPT200W36A4-A	72W	White	36*2W	ON/OFF
TPT200F36A4-A	96W	RGBW	36*2.7W	DMX512
TPT200W36A4-B	72W	White	36*2W	ON/OFF
TPT200F36A4-B	96W	RGBW	36*2.7W	DMX512
TPT200W36A4-C	72W	White	36*2W	ON/OFF
TPT200F36A4-C	96W	RGBW	36*2.7W	DMX512
TPT200W36A4-D	72W	White	36*2W	ON/OFF
TPT200F36A4-D	96W	RGBW	36*2.7W	DMX512
TPT200W36A4-E	72W	White	36*2W	ON/OFF
TPT200F36A4-E	96W	RGBW	36*2.7W	DMX512
TPT200W36A4-F	72W	White	36*2W	ON/OFF
TPT200F36A4-F	96W	RGBW	36*2.7W	DMX512
TPT200W36A4-G	72W	White	36*2W	ON/OFF
TPT200F36A4-G	96W	RGBW	36*2.7W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	AC100~240V
Size	Ø195mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/10°/15°/25°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%



Dimension




Distribution curve flux




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node





LED Spotlight

Outdoor spotlights play an indispensable role in modern urban landscape design with their unique charm and excellent performance. They are mainly used to illuminate trees, plants or building tiles. They are designed to highlight the shape and color of plants and the unique texture of buildings. The compact lamp body can exert huge light energy.

WL45 LED Spotlight



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
WL45W1D2	3W	White	3*1W	ON/OFF
WL45F1D2	4W	RGBW	4*1W	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Ø45*L80*H70mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	4°/5°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%

Dimension





Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;

Install Node



WL65 LED Spotlight



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
WL65W3D2	6W	White	3*2W	ON/OFF
WL65F3D2	9W	RGBW	3*3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Ø65*L105*H91mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	10°/30°/45°/15°25°/15°60°/20°45°/10°60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w ,RGBW 40lm/w
RH	30~80%




Dimension



Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;

Distribution curve flux



Install Node



SP65 LED Spotlight



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
SP65W1D2	5~15W	White	1*15W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC240V
Size	Ø65*L145/178*H380mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	20°/25°/40°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w
RH	30~80%



Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;



Distribution curve flux



Install Node



SP75 LED Spotlight



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
SP75W1D2	5~15W	White	1*15W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC240V
Size	Ø75*L190*H340mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	20°/25°/40°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w
RH	30~80%



Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;



Distribution curve flux



Install Node



SP90 LED Spotlight



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
SP90W1D2	10~30W	White	1*30W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC240V
Size	ø90*L165/220*H400mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	20°/25°/40°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;

Distribution curve flux



Install Node



SP108 LED Spotlight



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
SP108W1D2	30~50W	White	1*50W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V/AC240V
Size	Ø108*L238*H420mm
Housing Material	ADC12 + Tempered Glass
Warranty	5 Years
Beam Angle	20°/25°/40°/45°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w
RH	30~80%



Dimension




Product Features


- ※ Double-layer waterproof, IP66 grade;
- ※ The lamp body is made of high-strength ADC12 die-cast aluminum, with good thermal conductivity and excellent heat dissipation;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ The surface is treated with special outdoor powder and high-quality spraying process, which is corrosion-resistant and does not change color;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;




Distribution curve flux



Install Node





LED Inground Light

The underground wall washer is a widely evaluated lighting equipment for architectural landscape lighting. Its main function is to enhance the appearance beauty of the building through the focus or ground, highlight the texture of the building's skin, and create a unique light and shadow effect, Let the building be further sublimated at night.

MD25 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD25W48D2	12W	White	48*0.25W	ON/OFF
MD25F48D2	15W	RGBW	48*0.3W	DMX512
MD25MW60D2	15W	White	60*0.25W	ON/OFF
MD25MF60D2	18W	RGBW	60*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W25*H50mm
Housing Material	Al6063 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/20°/30°/45°/20*40°/110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, Ip67 grade;
- ※ Al6063 aluminum, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD60 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD60W24D2	24W	White	24*1W	ON/OFF
MD60W24D2	48W	White	24*2W	ON/OFF
MD60MW60D2	15W	White	60*0.25W	ON/OFF
MD60MF60D2	18W	RGBW	60*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W60*H77mm
Housing Material	Al6063 + Tempered Glass
Warranty	3 Years
Beam Angle	10°/15°/30°/45°/60°/15*25°/10*60°/110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, Ip67 grade;
- ※ Al6063 aluminum, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD72 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD72W24D2	24W	White	24*1W	ON/OFF
MD72W24D2	36W	White	24*1.5W	ON/OFF
MD72MW60D2	15W	White	60*0.25W	ON/OFF
MD72MF60D2	18W	RGBW	60*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1000*W68*H80mm
Housing Material	Al6063 + Tempered Glass
Warranty	3 Years
Beam Angle	10°/15°/30°/45°/60°/15*25°/10*60°/110°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD50 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD50F1D2	3W	RGB	3*1W	ON/OFF
MD50F1D2	3W	RGBW	3*1W	ON/OFF


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V
Size	Φ52*H52mm
Housing Material	Al6063 + Tempered Glass/PMMA
Warranty	3 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%



Dimension




Distribution curve flux



Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Install Node



MD85 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD85W3D2	3W	White	3*1W	ON/OFF
MD85F3D2	3W	RGB/RGBW	3*1W	DMX512
MD85W3D2B	6W	White	3*2W	ON/OFF
MD85F3D2B	6W	RGB/RGBW	3*2W	DMX512



Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Φ85*H95mm
Housing Material	SUS304 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/30°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%




Dimension




Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD130 LED Inground Light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
MD130W6D2	6W	White	6*1W	ON/OFF
MD130F6D2	6W	RGB/RGBW	6*1W	DMX512
MD130W6D2B	12W	White	6*2W	ON/OFF
MD130F6D2B	12W	RGB/RGBW	6*2W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Φ130*H95mm
Housing Material	SUS304 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/30°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%


Dimension




Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD160 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD160W9D2	9W	White	9*1W	ON/OFF
MD160F9D2	9W	RGB/RGBW	9*1W	DMX512
MD160W9D2B	18W	White	9*2W	ON/OFF
MD160F9D2B	18W	RGB/RGBW	9*2W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Φ160*H105mm
Housing Material	SUS304 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/30°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%




Dimension





Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD180 LED Inground Light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
MD180W12D2	24W	White	12*2W	ON/OFF
MD180F12D2	24W	RGB/RGBW	12*2W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Φ180*H125mm
Housing Material	SUS304 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/30°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%


Dimension





Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD210 LED Inground Light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
MD210W18D2	18W	White	18*1W	ON/OFF
MD210W18D2	18W	RGB/RGBW	18*1W	DMX512
MD210W18D2B	27W	White	18*1.5W	ON/OFF
MD210W18D2B	27W	RGB/RGBW	18*1.5W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Φ210*H120mm
Housing Material	SUS304 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/30°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%




Dimension





Product Features

- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node



MD230 LED Inground Light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
MD230W24D2	24W	White	24*1W	ON/OFF
MD230F24D2	24W	RGB/RGBW	24*1W	DMX512
MD230W18D2B	30W	White	18*2W	ON/OFF
MD230F18D2B	30W	RGB/RGBW	18*2W	DMX512

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	Φ230*H135mm
Housing Material	SUS304 + Tempered Glass
Warranty	3 Years
Beam Angle	15°/30°/60°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 40lm/w ,RGBW 15lm/w
RH	30~80%


Dimension





Product Features


- ※ Double-layer waterproof, IP68 grade;
- ※ 304 stainless steel, high light transmittance tempered glass;
- ※ Adopt high-quality optical lens, the light output is uniform and accurate;
- ※ Adopt high-quality LED, high color rendering, high brightness and uniform color;
- ※ Anti-aging silicone seal;
- ※ Waterproof male and female connectors, rubber wire, simple wiring;
- ※ Standard DMX512 protocol, strong compatibility.

Distribution curve flux



Install Node






LED Guide Panel Light

LED light guide plate is a device used to optimize the distribution of LED light sources and improve light utilization. It is typically made of transparent or translucent materials with a special surface structure to alter and guide the light emitted by the LEDs. The LED light guide plate is employed to enhance the light distribution of illumination devices, ensuring that the light is uniformly spread across the illuminated area, thereby reducing shadows and spots.

DG600 LED guide panel light



Electrical & output data


Item No.	Power	Color	LED Qty	Control method
DG600W48D2	12W/M	white	48*0.25W	ON/OFF
DG600F48D2	15W/M	RGBW	48*0.3W	DMX512

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L1*L2*H20mm
Housing Material	Al6063 + PMMA
Warranty	3 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 50lm/w ,RGBW 20lm/w
RH	30~80%

Dimension




Distribution curve flux



Product Features

- ※ Use transparent plates with a light transmittance of more than 92%-93%;
- ※ Can be made into special shapes, such as round, oval, arc, triangle, rectangle, etc. to meet different design requirements;
- ※ Can achieve ultra-thin, ultra-bright, and uniform light guide effects;
- ※ No dark areas, simple and quick installation and maintenance.

Install Node



DG430 LED guide panel light



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
DG430F24D2	7W	RGB	24*0.3W	DMX512
DG580F36D2	12W	RGB	36*0.3W	DMX512
DG730F42D2	15W	RGB	42*0.3W	DMX512
DG880F54D2	18W	RGB	54*0.3W	DMX512


Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L=430/580/730/880mm
Housing Material	Al6063 + PMMA
Warranty	3 Years
Beam Angle	120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 50lm/w ,RGBW 20lm/w
RH	30~80%




Distribution curve flux




Product Features


- ※ Use transparent plates with a light transmittance of more than 92%-93%;
- ※ Can be made into special shapes, such as round, oval, arc, triangle, rectangle, etc. to meet different design requirements;
- ※ Can achieve ultra-thin, ultra-bright, and uniform light guide effects;
- ※ No dark areas, simple and quick installation and maintenance.

Install Node



Dimension





LED Street Light

Low-altitude lighting fixtures solve the problem of installing elevated bridge street lamp poles. At night, the light is evenly projected on the road to form a uniform light belt. The clever light distribution design is used to improve the road illumination while avoiding glare, achieving an organic combination of functional lighting and decorative lighting, and a harmonious unity of light and environment.



Electrical & output data

Item No.	Power	Color	LED Qty	Control method
HL200W6D2	12W	white	6*2W	ON/OFF
HL200W12D2	18W	white	12*1.5W	ON/OFF

Installation Indication

Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.


Voltage	DC24V
Size	L200*L115*H151mm
Housing Material	Al6063 + Tempered Glass
Warranty	5 Years
Beam Angle	10*120°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w
RH	30~80%




Product Features

- ※ Accurate light distribution, uniform light output without glare.
- ※ Optical grade high-transmittance material is selected, high light efficiency
LED has good light output rate,
- ※ The embedded parts are 4mm thick, high strength, anti-deformation and good firmness.
- ※ The surface of the lamp is treated with Akzo Nobel anti-ultraviolet polyester powder electrostatic spraying.
- ※ 2.0 ultra-high thermal conductivity LED aluminum substrate is used, and it is resistant to high and low temperatures and super waterproof special joints.


Distribution curve flux



Install Node



Dimension





Electrical & output data


Item No.	Power	Color	LED Qty	Control method
HL300W7D2	15W	white	7*2.5W	ON/OFF

Installation Indication


Residential buildings, commercial properties, office buildings, museums, religious buildings, industrial parks, bridges, villas, parks, etc.

Voltage	DC24V
Size	L343*L113*H74mm
Housing Material	Al6063 + Tempered Glass
Warranty	5 Years
Beam Angle	10*80°
CRI	>80
SDCM	<5
Ambient temperature	Tamin=-20 °C , Tamax=55 °C
Luminous efficiency	WHITE 80lm/w
RH	30~80%


Dimension



Distribution curve flux



Install Node



- ※ Accurate light distribution, uniform light output without glare.
- ※ Optical grade high-transmittance material is selected, high light efficiency
LED has good light output rate,
- ※ The embedded parts are 4mm thick, high strength, anti-deformation and good firmness.
- ※ The surface of the lamp is treated with Akzo Nobel anti-ultraviolet polyester powder electrostatic spraying.
- ※ 2.0 ultra-high thermal conductivity LED aluminum substrate is used, and it is resistant to high and low temperatures and super waterproof special joints.



Shenzhen Liangjia Beauty Lighting Co., Limited

Add: 6F, Building H, innovation Cloud Valley, No. 48Paotai Road,
Guangming district, Shenzhen, China

Tel: +86-0755-29756055

Website: www.ljmlamp.com

Email: kenguan16@ljmlamp.com

